

SPECIFIC RADIO TUNE-UPS (Cont'd):

Pace 8155 MM55107N:

RX: R549; Squelch Range.  
R544; S Meter.

TX: Peak L401, T401, T402, T403, L404, L407, L408 and C432.  
R310; AMC.  
R425; RF Power Meter.  
L202; VCO Coil; C212-VCO XMIT.

Zapper will install @ C226 for extra Channels.

President AR-7 TC9106P:

RX: VR1; Squelch Range.  
VR2; S Meter.

TX: Peak L9, L10, L12, L16.  
VR3; RF Power Meter.  
L3; VCO Coil.

Remove TR17, AMC Limiter.

President 1015001 James K. D2814C:

RX: VR1; If Gain.  
VR3; Squelch Range.

TX: Peak L12, L13, L14, L15, L17-L20 is T.V.I.  
VR2; AMC  
L10 VCO Coil.

Zapper will install @ C72 and adjust L8 for extra Channels.

President AX-711 (TC9106P):

TX: Peak L20, L10, L13, L14.  
VR5; AM Mod.  
VR3; RF Power Meter.  
VR1; S Meter.

Realistic TRC205 WT:

RX: VR101; Squelch Range.  
VR104; S Meter.

TX: Adjust T9, L300, L301, L302, L303 and L100 for Max. RF output.  
VR300; Controlled Carrier Bias.  
VR103; RF Meter.  
Modulation-Remove TR306.