



(REVISION A)

SEMICONDUCTOR	TERMINAL CONNECTION	(BOTTOM VIEW UNLESS OTHERWISE NOTED)
2SA719	TOP VIEW	TOP VIEW
2SC829	TOP VIEW	TOP VIEW
2SC829B	TOP VIEW	TOP VIEW
2SC839	TOP VIEW	TOP VIEW
2SC1318	TOP VIEW	TOP VIEW
2SC1359	TOP VIEW	TOP VIEW
2SC1215	TOP VIEW	TOP VIEW
2SC710	TOP VIEW	TOP VIEW
2SC784	TOP VIEW	TOP VIEW
2SC372	TOP VIEW	TOP VIEW
2SC1687	TOP VIEW	TOP VIEW
2SC1688	TOP VIEW	TOP VIEW
2SC1306	TOP VIEW	TOP VIEW
2SC1678	TOP VIEW	TOP VIEW
2SC1760	TOP VIEW	TOP VIEW
2SC1957	TOP VIEW	TOP VIEW
TA7205P	TOP VIEW	TOP VIEW
BA521	TOP VIEW	TOP VIEW

- NOTES:**
- All resistors are 10%, 1/4 watt, with value given in ohms, unless specified otherwise.
  - All capacitor values are given in uF, unless specified otherwise.
  - Symbols used:
    - ⊖ - chassis ground
    - ⊕ - p.c. board ground
    - \* - indicates component value may vary from unit to unit
    - ★ - numbered wires on schematic pages have no reference to electronic components, but are for ease in tracing wiring only

Figure 3-12. Schematic Diagram, Main P.C. Board, Model 2679A-X