



NOTES:

1. All resistors are 5%, 1/4 watt, with value given in ohms, unless specified otherwise.
2. All capacitor values are given in uF, unless specified otherwise.
3. Symbols used:
 - ⊖ - chassis ground
 - ⊔ - p.c. board ground
 - * - indicates component value may vary from unit to unit
 - ⊛ - numbered wires on schematic pages have no reference to electronic components, but are for ease in tracing wiring only.

SEMICONDUCTOR	TERMINAL CONNECTION	(BOTTOM VIEW UNLESS OTHERWISE NOTED)
2SC710	SEE SIDE VIEW	SEE SIDE VIEW
2SC784	SEE SIDE VIEW	SEE SIDE VIEW
2SC372	SEE SIDE VIEW	SEE SIDE VIEW
2SC1687	SEE SIDE VIEW	SEE SIDE VIEW
2SC1688	SEE SIDE VIEW	SEE SIDE VIEW
2SC1306	SEE SIDE VIEW	SEE SIDE VIEW
25C1678	SEE SIDE VIEW	SEE SIDE VIEW
2SC1760	SEE SIDE VIEW	SEE SIDE VIEW
25C1957	SEE SIDE VIEW	SEE SIDE VIEW
TA7205P	SEE SIDE VIEW	SEE SIDE VIEW
BA521	SEE SIDE VIEW	SEE SIDE VIEW

Figure 3-6. Schematic Diagram, Main P.C. Board, Model 2679A