



RESISTANCE READINGS

ITEM	TUBE	Pin 1	Pin 2	Pin 3	Pin 4	Pin 5	Pin 6	Pin 7	Pin 8	Pin 9
V1	6GH8	170K	3.3meg	13000Ω	FIL	FIL	13000Ω	0Ω	1000Ω	250K
V2	6GH8	122K	2meg	13000Ω	FIL	FIL	13000Ω	0Ω	0Ω	100K
V3	6GH8	147K	1meg	13200Ω	FIL	FIL	13200Ω	0Ω	0Ω	47K
V4	6GH8	148K	9Ω	13000Ω	FIL	FIL	13000Ω	470Ω	9000Ω	2meg
V5	6T8A	150K	47K	1.6meg	FIL	FIL	0Ω	0Ω	1.7meg	1meg
V6	12AB5	11000Ω	NC	47K	FIL	FIL	47K	450Ω	1100Ω	110Ω
V7	6CZ5	115K	NC	22K	FIL	FIL	22K	0Ω	NC	140Ω

ALL READINGS MADE IN "RECEIVE" POSITION UNLESS OTHERWISE DESIGNATED.
 † MEASURED FROM OUTPUT OF X6. • TAKEN IN "TRANSMIT" POSITION.
 ■ MEASURED AT FINAL AMP PLATE CURRENT TEST RECEPTACLE. NC NO CONNECTION

A PHOTOFACIT STANDARD NOTATION SCHEMATIC
 ©Howard W. Sams & Co., Inc. 1963

PEARCE-SIMPSON MODEL COMPANION